

THE UNITED STATES OF AMERICA

TO ALL TO WHOM THESE PRESENTS SHALL COME:

PCT/IB04/52782

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

REC'D 15 DEC 2004

WIPO

PCT

February 03, 2004

THIS IS TO CERTIFY THAT ANNEXED HERETO IS A TRUE COPY FROM THE RECORDS OF THE UNITED STATES PATENT AND TRADEMARK OFFICE OF THOSE PAPERS OF THE BELOW IDENTIFIED PATENT APPLICATION THAT MET THE REQUIREMENTS TO BE GRANTED A FILING DATE UNDER 35 USC 111.

APPLICATION NUMBER: 60/529,585

FILING DATE: December 15, 2003

**PRIORITY
DOCUMENT**

SUBMITTED OR TRANSMITTED IN
COMPLIANCE WITH RULE 17.1(a) OR (b)



**By Authority of the
COMMISSIONER OF PATENTS AND TRADEMARKS**

P. Swain

P. SWAIN

Certifying Officer

13049 U.S. PTO
121503

Please type a plus sign (+) inside this box → ☐ +

2


PTO/SB/16 (02-01)
Approved for use through 10/31/2002. OMB 0651-0032
Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION FOR PATENT under 37 CFR 1.53 (c).

Express Mail Label N . EV 312 068 652

Date of Deposit: December 15, 2003

INVENTOR(S)					
Given Name (first and middle [if any])		Family Name or Surname		Residence (City and either State or Foreign Country)	
Wilhelmus Joseph		ROSENDAAL		Eindhoven, Netherlands	
<input type="checkbox"/> Additional inventors are being named on the _____ separately numbered sheets attached hereto					
TITLE OF THE INVENTION (280 characters max)					
PROJECTOR AND METHOD OF PROJECTING AN IMAGE HAVING MULTIPLE IMAGE SIZES					
CORRESPONDENCE ADDRESS					
Direct all correspondence to:					
<input checked="" type="checkbox"/> Customer Number		24737		<div style="border: 1px solid black; padding: 5px; text-align: center;"> *24737*  </div>	
OR		Type Customer Number here			
<input checked="" type="checkbox"/> Firm or Individual Name		U. S. PHILIPS CORPORATION			
Address		P. O. BOX 3001			
Address					
City	BRIARCLIFF MANOR	State	NY	ZIP	10510
Country	USA	Telephone	(914) 945-6000	Fax	(914) 332-0615
ENCLOSED APPLICATION PARTS (check all that apply)					
<input checked="" type="checkbox"/> Specification Number of Pages		15		<input type="checkbox"/> CD(s), Number	
<input checked="" type="checkbox"/> Drawing(s) Number of Sheets		1		<input type="checkbox"/> Other (specify)	
<input type="checkbox"/> Application Data Sheet. See 37 CFR 1.76					
METHOD OF PAYMENT OF FILING FEES FOR THIS PROVISIONAL APPLICATION FOR PATENT (check one)					
<input type="checkbox"/> Applicant claims small entity status. See 37 CFR 1.27.					
<input type="checkbox"/> A check or money order is enclosed to cover the filing fees					
<input checked="" type="checkbox"/> The Commissioner is hereby authorized to charge filing fees or credit any overpayment to Deposit Account Number:				14-1270	
<input type="checkbox"/> Payment by credit card. Form PTO-2038 is attached.				FILING FEE AMOUNT (\$) 160.00	
The invention was made by an agency of the United States Government or under a contract with an agency of the United States Government.					
<input checked="" type="checkbox"/> No.					
<input type="checkbox"/> Yes, the name of the U.S. Government agency and the Government contract number are: _____					

Respectfully submitted,

SIGNATURE



Date

December 15, 2003

TYPED or PRINTED NAME

ERIC M. BRAM

REGISTRATION NO.: 37,285

(if appropriate)

Docket Number:

US 030504

TELEPHONE

(914) 333-9635

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

This collection of information is required by 37 CFR 1.51. The information is used by the public to file (and by the PTO to process) a provisional application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 8 hours to complete, including gathering, preparing, and submitting the complete provisional application to the PTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, Washington, D.C., 20231. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Box Provisional Application, Assistant Commissioner for Patents, Alexandria, VA 22313.

PROJECTOR AND METHOD OF PROJECTING AN IMAGE
HAVING MULTIPLE IMAGE SIZES

5 This invention pertains to the image projectors, and in particular, to front projection display systems wherein a size of a displayed image may be varied.

 Front projection display systems are gaining increasing popularity as their prices decrease, and both image quality and illumination intensity improve. Under proper
10 lighting conditions, front projection display systems are capable of displaying excellent-quality video images at large sizes (e.g., 120" diagonal) that are not generally possible or practical with other types of conventional display systems (e.g., a cathode ray tubes, rear projection displays, plasma displays, liquid crystal displays, etc.). Front projection display systems are especially popular for displaying video content such as movies and sports in a
15 large format. In the past, such front projection display systems have mainly been used in home theaters, basements, living rooms, and other larger viewing areas where it was desired to provide a "home cinema" experience with a very large displayed image.

 Meanwhile, as the image quality and illumination intensity improve, and as prices decrease, it is becoming possible for many people to consider a front projection display
20 system as a replacement unit for a "normal" television display, such as a cathode ray tube display, a rear projection display, or a plasma display device, in the living room, family room, etc.

 However, for a variety of reasons, viewers do not always want to view a video program displayed in a large format (e.g., 120" diagonal). For example, violent images in
25 news programs, frightening animated cartoon characters, etc. may be too upsetting, (especially to small children) if displayed at such a large size. Also, at the same time that one or more people may be watching a news program or other television program displayed by a front projection display system, other people in the same room may be engaged in other activities such as conversation, game playing, reading, etc. In that case, a
30 gigantic image (e.g., 120" diagonal) may be distracting or disturbing to these other activities.

 In these cases, users would prefer to view the video content in a more traditional, "normal" size (e.g., 28" diagonal).

Furthermore, although the illumination intensity of front projection display systems continues to improve, a high level of background or ambient light still makes it difficult to view large format images displayed by these systems. Therefore, it is typically necessary to close curtains and/or dim the room lights in order to view larger-sized images displayed by front projection display systems.

Although people may be willing to close the curtains and/or dim (or turn off) all lights in a room in order to watch a special sporting event or a movie in a "cinema" setting, they do not want to have to always have to do this even when they just want to watch a news program, weather forecast, game show, etc. And it is not generally desired anyway to watch news and most other "normal" television programs in 120" size format.

Furthermore, as noted above, at the same time that one or more people may be watching a regular television program displayed by a front projection display system, other people in the same room may be engaged in other activities such as conversation, game playing, reading, etc. In that case, dimming the lights or turning them off completely may make it difficult if not impossible for those other people to engage in or enjoy these activities.

As a result, there is a hindrance to the adoption of existing front projection display systems as "television replacement" displays for more generally viewing all sorts of video programs in a variety of environments.

Accordingly, it would be desirable to provide a projection display system capable of selectively operating in either a "normal" television-replacement mode (wherein it projects a smaller-sized image), or in a large-format "cinema" projection mode (wherein it projects a larger-sized image). It would also be desirable to provide such a system that can automatically select between two different display sizes for displaying an image, based upon one or more predetermined criteria, such as ambient light level, program content, video source, etc. It would be further desirable to provide a method of projecting an image that provides an automatic selection and/or a user selection between a large-sized format and a smaller, "normal television" sized format. It would further be desirable to provide a projection display system which can provide greater daylight viewing possibilities by concentrating all of the light into a smaller-sized (e.g., 28") image. The present invention is directed to addressing one or more of the preceding concerns.

In one aspect of the invention, a projection display system comprises a light source producing light; a light modulator adapted to generate an image from the light produced by the light source; a projection lens system adapted to project the image onto an image projection surface; memory for storing first data representing a first display size for the projected image on the image projection surface and second data representing a second display size for the projected image on the image projection surface; and a controller adapted to retrieve one of the first and second data from the memory and, in response thereto, to control the projection lens system to cause the projected image to have a corresponding one of the first and second display sizes on the image projection surface.

10 In another aspect of the invention, a method of projecting an image with a projection display system, comprises generating an image; selectively retrieving from memory either first data, representing a first display size on an image projection surface, or second data representing a second display size on the image projection surface, and in response to the retrieved data, projecting the image onto the image projection surface at a
15 corresponding one of the first and second display sizes.

In yet another aspect of the invention, a projection display system comprises: a light source for producing light; means for generating an image from the light produced by the light source; projection means for projecting the image onto an image projection surface; means for detecting an ambient light level present in an area where the projection display
20 system is located; and control means adapted to control the projection means to change a size of a projected image on the image projection surface in response to the detected ambient light level.

FIG. 1 shows block diagram of a first embodiment of a front projection display system according to one or more aspects of the present invention.

25 FIG. 1 shows a block diagram of a first embodiment of a front projection display system 100.

The front projection display system 100 comprises a light source 110, a light modulator 120, a projection lens system 130, a controller 140, memory 145, a sensor 160, a user input 170, one or more video inputs 175, and a video processor 180. A display screen
30 or image projection surface 150 may be provided as part of the front projection display system 100, or may be separately provided, for example, as nothing more than a living

room wall upon which an image is projected and displayed, as explained in more detail below.

The light source 110 may comprise an incandescent or fluorescent bulb, one of more light emitting diodes, or other convenient light emitter. Beneficially, the light source
5 110 includes reflectors, mirrors, and/or lenses to produce a light beam having a desired size, aspect ratio, color point, illumination distribution profile, intensity, etc., and to direct the produced light toward the light modulator 120.

The light modulator 120 may be a liquid crystal light modulator comprising one or more (e.g., three) liquid crystal devices arranged to image light in accordance with a
10 supplied video signal and to produce a combined image comprising colored light. However, other types of light modulators 120 are also envisioned, such as a digital micromirror device (DMD).

The projection lens system 130 comprises a means for adjusting a display size of an image projected onto the projection lens system 130 in response to a control signal from
15 the controller 140, and, beneficially, also under manual control. In one embodiment, the projection lens system 130 includes a motor-driven zoom lens that changes the display size based upon the control signal from the controller 140. In another embodiment, the projection lens system 130 includes a plurality of lenses that may be selectively moved into or out of an optical path of imaged light from the light modulator, in response to the control
20 signal from the controller 140, to thereby change a magnification and vary a display size. Beneficially, the light modulator 120 and projection lens system 130 may include and operate with a scanning laser beam.

Beneficially, the controller 140 includes a processor executing a set of instructions to control various aspects of the front projection display system 100 as will be discussed in
25 more detail below. Beneficially, the sensor 160 is a light sensor adapted to detect ambient light in an area where the front projection display system 100 is located. The user input 170 may include an infrared remote control sensor input, as well as one or more manual controls (e.g., switches, buttons, etc.) provided on the main body of the front projection display system 100, as will be discussed in further detail below.

30 The front projection display system 100 may have one video input 175, but beneficially includes a plurality of video inputs 175, which may conform to a variety of different video interface standards. For example, one video input 175 may adapted to

receive video signals in a component video format. A second video input 175 may adapted to receive video signals in an RGB format. A third video input 175 may adapted to receive video signals in an "S-video" format. A fourth video input 175 may adapted to receive video signals in a composite video format. Any and all combinations are possible.

5 Operation of the front projection display system 100 will now be described.

Light source 110 produces light having a desired size, aspect ratio, color point, illumination distribution profile, intensity, etc., and directs the produced light toward the light modulator 120. Meanwhile, one or more video signals representing an image or sequence of images to be displayed is/are received at one or more video inputs 175.

10 When the front projection display system 100 has a plurality of video inputs 175, then a switch in the video processor 180 responds to a control signal from the controller 140 and selects a video signal for display (or two video signals in the case of picture-in-picture display mode). The video processor 180 may process the selected video signal(s) as desired and then provide a processed video signal to the light modulator 120.

15 Light modulator 120 generates an image from the light produced by the light source 110, in accordance with the video signal received from the video processor 180. Light modulator 120 provides the image to the projection lens system 130. Projection lens system 130 enlarges and formats the image for display on the image projection surface 150 (e.g. a wall of a room, a projection screen, etc.), in response to a display size selection control signal received from the controller 140, as will be explained in further detail below.

20 The controller 140 operates together with the projection lens system 130 to select between projecting the image onto the image projection surface 150 in either a first, larger-format, display size for providing a "cinema" viewing experience, or a second, smaller-format, display size for providing a "normal" television viewing experience. The projection lens system 130 is adapted to switch between two display sizes that vary greatly in size, in response to a control signal from the controller 140. Beneficially, the ratio of the diagonal dimension of the first display size to the diagonal dimension of the second display size is at least 3:1. In that case, the first display size may have a diagonal dimension of 120 inches, and the second display size may have a diagonal dimension of 28 inches.

25 Beneficially, with the smaller display size, all of the light energy may be put into the smaller area to produce a brighter image. In that case, the light intensity for images projected at the second display size (e.g., 28") may be such that the image is easily

viewable with good quality in a room with a moderate level of ambient light (e.g., daylight conditions), while images projected at the first display size (e.g., 120") may require a darkened room with low ambient light in order to be easily viewable with good quality.

Beneficially, the first and second display sizes may be chosen or determined by a user or an installer when the front projection display system 100 is installed in a room, for example based upon the dimensions, layout, or other characteristics of the room in which the front projection display system 100 is installed. The projection lens system 130 is adapted to be adjustable to change the size of a displayed image. As explained above, such adjustment may be made, for example, by controlling a motor-driven zoom lens, by selectively moving one or more lens(es) into or out of an optical path of imaged light from the light modulator 120, or other convenient method, to thereby change a magnification of the projection lens system 130 and vary the display size of a displayed image.

Once a first desired display size is determined by the user or installer by adjusting the a magnification of the projection lens system 130, a button may be pressed on the main body of the front projection display system 100, on a remote control unit, etc., to indicate that the current configuration should be remembered or stored as the first display size. Beneficially, in response to receiving such an indication via user input 170, first data representing the chosen first display size, and the corresponding configuration of the projection lens system 130 necessary to produce the chosen first display size, is stored in memory 145. Then, the projection lens 130 is once again adjusted to change the size of a displayed image. Once a second desired display size is determined by the user or installer, a button may be pressed on either the main body of the front projection display system 100, or a remote control unit, etc., to indicate that the current configuration should be remembered or stored as the second display size. Beneficially, in response to receiving such an indication via user input 170, second data representing the chosen second display size, and the corresponding configuration of the projection lens system 130 necessary to produce the chosen second display size, is stored in memory 145. Optionally, the first and second display sizes may be changed (reprogrammed) as desired by a user command received via the user input 170.

Various embodiments of a selection means and method for selecting between the first and second display sizes will now be explained.

In one embodiment, a user manually selects whether she/he wants to view a program in a first, larger-format display size for providing a "cinema" viewing experience, or a second, smaller-format display size for providing a "normal" television viewing experience. In this case, selection between the first and second display sizes may be made
5 "manually" by a size selection indication received from a user via user input 170. For example, user input 170 may include a switch or selection button on the main body of the front projection display system 100, on a remote control unit, etc., for switching between the first and second display sizes (e.g., a button or switch labeled "Cinema/Normal"). In response to a size selection indication received via the user input 170, controller 140
10 retrieves the corresponding data, representing either the first display size or the second display size, from memory 145. The controller 140 then retrieves the corresponding data from memory 145, and provides a display size selection control signal to the projection lens system 130, causing the projection lens system 130 to project an image received from the light modulator 120 with the selected display size (i.e., in either the first display size or
15 the second display size).

In another embodiment, the display size is selected automatically by the front projection display system 100 based on one or a combination of predetermined criteria.

In one case, light sensor 160 detects a level of ambient light present in the area where the front projection display system 100 is located and provides a signal to the
20 controller 140 indicating the ambient light level. The controller 140 may compare the ambient light level to a threshold (fixed or user-selectable) and in response thereto, select either the first (larger) display size for providing a cinema viewing experience, or the second (smaller) display size for providing a "normal" television viewing experience. The controller 140 then retrieves the corresponding data from memory 145, and provides a
25 corresponding display size selection control signal to the projection lens system 130.

In a second case, the front projection display system 100 determines which one of the video inputs 175 has been selected for display, and in response thereto, selects either the first (larger) display size for providing a cinema viewing experience, or the second, (smaller) display size for providing a "normal" television viewing experience. For
30 example, if it is determined that the selected video input is of a type that is or would normally be connected to a DVD player, then the front projection display system 100 automatically selects the first (larger) display size for providing a cinema viewing

experience. On the other hand, if it is determined that the selected video input is of a type that is or would normally be connected to a television (e.g., terrestrial broadcast) receiver, then the front projection display system 100 automatically selects the second (smaller) display size for providing a normal television viewing experience. The controller 140 may
5 determine which video source is selected for display, and in response thereto select either the first (larger) display size for providing a cinema viewing experience, or the second (smaller) display size for providing a "normal" television viewing experience. The controller 140 then retrieves the corresponding data from memory 145, and provides a corresponding display size selection control signal to the projection lens system 130.

10 In a third case, the front projection display system 100 determines a program type of an image or video signal being displayed, and in response thereto, selects either the first (larger) display size for providing a cinema viewing experience, or the second (smaller) display size for providing a "normal" television viewing experience. For example, if it is determined that the video program that is being displayed is a movie, then the front
15 projection display system 100 selects the first (larger) display size for providing a cinema viewing experience. On the other hand, if it is determined that the video program that is being displayed is a news program, then the front projection display system 100 automatically selects the second (smaller) display size for providing a normal television viewing experience. The controller 140 may determine the video program type from a
20 program ID received in a program guide provided to the projection display system 100 from a video source (e.g., a cable decoder or a satellite receiver or terrestrial broadcast receiver), or from information embedded in the video signal (e.g., vertical blanking interval (VBI) data such as teletext, etc.). In response to this information, the controller 140 may
25 select either the first (larger) display size for providing a cinema viewing experience, or the second (smaller) display size for providing a "normal" television viewing experience. The controller 140 then retrieves the corresponding data from memory 145, and provides a corresponding display size control signal to the projection lens system 130.

In a fourth case, the front projection display system 100 analyzes the content of the image or video signal being displayed (e.g., color patterns; movement; etc.), and in
30 response thereto, selects either the first (larger) display size for providing a cinema viewing experience, or the second (smaller) display size for providing a "normal" television viewing experience. For example, if it is determined that the video program that is being

displayed involves a lot of motion or appropriate color patterns, it may be surmised that the program is a movie, in which case, the front projection display system 100 selects the first (larger) display size for providing a cinema viewing experience. On the other hand, if it is determined that the video program that is being displayed involves little or no motion or,
5 has other particular color patterns, it may be surmised that the program is a "talking head" type show, in which case the front projection display system 100 automatically selects the second (smaller) display size for providing a normal television viewing experience. The controller 140 may perform the video/image content analysis, and in response thereto may retrieve the corresponding data from memory 145, and provide a corresponding display
10 size control signal to the projection lens system 130.

Beneficially, the front projection display system 100 comprises an electronic sub-circuit (which may be separate from or part of the controller 140) to analyze the input data stream such that the type of content can be determined and the best suitable display size is automatically selected. Alternatively, the electronic sub-circuit may analyze the content of
15 the data input to the display system to determine an advised screen size present (e.g., embedded) in the data input stream at a predetermined location.

Alternatively, the information used in the four cases described above may be combined in various ways to make an automated decision as to whether to select either the first (larger) display size for providing a cinema viewing experience, or the second
20 (smaller) display size for providing a "normal" television viewing experience.

Beneficially, in the second embodiment (automatic display size selection), a manual override feature is included that allows a user to manually select a display size and override the automatic selection made by the front projection display system 100.

Accordingly, the front projection display system 100 is capable of selectively
25 operating in either a "normal" television-replacement mode (wherein it projects a smaller-sized image), or in a large-format "cinema" projection mode (wherein it projects a larger-sized image). Beneficially, it can select between two different display sizes for displaying an image under user control and/or automatically based upon one or more predetermined criteria, such as ambient light level, program content, video source, etc. It also provides
30 greater daylight viewing possibilities by concentrating all of the light into a smaller-sized (e.g., 28") image for programs like the evening news, where a large sized format (e.g., 120") is not desired.

While embodiments are disclosed herein, many variations are possible which remain within the concept and scope of the invention. For example, although the embodiments described above determine and store data for only two display sizes, it may be beneficial in some cases to provide for three - or some other convenient number of -
5 display sizes. Such variations would become clear to one of ordinary skill in the art after inspection of the specification, drawings and claims herein. The invention therefore is not to be restricted except within the spirit and scope of the appended claims.

CLAIMS:

1. A projection display system (100), comprising:
a light source (110) producing light;
5 a light modulator (120) adapted to generate an image from the light produced by the light source (110);
a projection lens system (130) adapted to project the image onto an image projection surface (150);
memory (145) for storing first data representing a first display size for the projected
10 image on the image projection surface (150) and second data representing a second display size for the projected image on the image projection surface (150); and
a controller (140) adapted to retrieve one of the first and second data from the memory (145) and, in response thereto, to control the projection lens system (130) to cause the projected image to have a corresponding one of the first and second display sizes on the
15 image projection surface (150).
2. The projection display system (100) of claim 1, further comprising a sensor (160) adapted to detect an ambient light level present in an area where the projection display system (100) is located, and wherein the controller (140) selects one of the first and
20 the second display sizes in response to the detected ambient light level.
3. The projection display system (100) of claim 1, further comprising a user input (170) adapted to receive a size selection indication from a user, and wherein the controller (140) selects one of the first and the second display sizes in response to the size selection
25 indication from the user.
4. The projection display system (100) of claim 1, wherein the controller (140) controls the projection lens system (130) to cause the projected image to have one of the first and the second display sizes on the image projection surface (150) in response to one
30 selected from a group consisting of: a source format of the image; a type of source device providing the image to the projection display system; and a program type for the image.

5 5. The projection display system (100) of claim 1, wherein a ratio of a diagonal dimension of the first display size to a diagonal dimension of the second display size is at least 3:1.

10 6. The projection display system (100) of claim 1, where the projection lens system (130) includes a zoom lens adapted to change the size of the projected image in response to the controller (140).

15 7. The projection display system (100) of claim 1, where the projection lens system (130) includes a means for selectively moving at least one lens into or out of an optical path of the image received from the light modulator (120) in response to the controller (140).

20 8. A projection display system (100) according to any of the preceding claims wherein the projection lens system (130) includes a scanning laser beam.

25 9. A projection display system (100) according to any of the preceding claims wherein the first data or second data representing the display size is selected by the controller (140) analyzing electronic data input to be displayed.

30 10. A method of projecting an image with a projection display system (100), comprising:
 generating an image;
 selectively retrieving from memory (145) either first data, representing a first display size on an image projection surface (150), or second data, representing a second display size on the image projection surface (150); and
 in response to the retrieved data, projecting the image onto the image projection surface (150) at a corresponding one of the first and second display sizes.

35 11. The method of claim 10, further comprising:
 detecting an ambient light level present in an area where the projection display system (100) is located; and

selecting one of the first and the second display sizes in response to the detected ambient light level.

12. The method of claim 10, further comprising:
5 receiving a size selection indication from a user; and
selecting one of the first and the second display sizes in response to the size selection indication from the user.

13. The method of claim 10, further comprising:
10 determining one of a source format of the image; a type of source device providing the image to the projection display system; and a program type for the image; and
selecting one of the first and the second display sizes in response to the determined one of the source format, the type of source device, and the program type.

15 14. The method of claim 10, wherein a ratio of a diagonal dimension of the first display size to a diagonal dimension of the second display size is at least 3:1.

15. The method of claim 10, wherein projecting the image onto the image projection surface (150) at a corresponding one of the first and second display sizes.
20 comprises adjusting a magnification of a zoom lens.

16. The method of claim 10, projecting the image onto the image projection surface (150) at a corresponding one of the first and second display sizes comprises selectively moving at least one lens into or out of an optical path of the projected image.
25

17. A projection display system (100), comprising:
a light source (110) for producing light;
means (120) for generating an image from the light produced by the light source (110);
30 projection means (130) for projecting the image onto an image projection surface (150);

means for detecting an ambient light level present in an area where the projection display system (100) is located; and

control means (140) adapted to control the projection means (130) to change a size of a projected image on the image projection surface (150) in response to the detected ambient light level.

18. The projection display system (100) of claim 17, wherein the control means (140) is also adapted to select a size of a projected image in response to size selection input signal from a user, regardless of the detected ambient light level.

19. The projection display system (100) of claim 17 wherein the projection means (130) is adapted to project the image at the first and second display sizes wherein a ratio of a diagonal dimension of the first display size to a diagonal dimension of the second display size is at least 3:1.

20. The projection display system (100) of claim 17, where the projection means (130) includes a zoom lens adapted to change the size of the projected image in response to the control means (140).

21. The projection display system (100) of claim 17, where the projection means (130) includes a means for selectively moving at least one lens into or out of an optical path of the projected image. .

22. The projection display system (100) of claim 17, where the means (120) for generating an image includes one of a liquid crystal device or a digital micromirror device (DMD).

ABSTRACT

A front projection display system (100) selectively operates in either a "normal" television-replacement mode, which projects a smaller-sized image, or in a large-format "cinema" projection mode with a larger-sized image. A display size selection can be made automatically according to factors such as ambient light level, and/or manually under user control. In response to the display size selection, a controller (140) retrieves appropriate data from memory (145), and controls a projection lens system (130) to display an image on an image projection surface (150) in either a first, larger-sized, format or in a second, smaller-sized format.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of

Atty. Docket

WILHELMUS JOSEPH ROSENDAAL

US 030504

Serial No.

Filed: CONCURRENTLY

Title: PROJECTOR AND METHOD OF PROJECTING AN IMAGE HAVING MULTIPLE
IMAGE SIZES

Commissioner for Patents
Alexandria, VA 22313

APPOINTMENT OF ASSOCIATES

Sir:

The undersigned Attorney of Record hereby revokes all
prior appointments (if any) of Associate Attorney(s) or Agent(s) in
the above-captioned case and appoints:

ERIC M. BRAM

(Registration No. 37,285)

c/o U.S. PHILIPS CORPORATION, Intellectual Property Department,
P.O. BOX 3001, Briarcliff Manor NY 10510, his Associate
Attorney(s)/Agent(s) with all the usual powers to prosecute the
above-identified application and any division or continuation
thereof, to make alterations and amendments therein, and to
transact all business in the Patent and Trademark Office connected
therewith.

ALL CORRESPONDENCE CONCERNING THIS APPLICATION AND THE
LETTERS PATENT WHEN GRANTED SHOULD BE ADDRESSED TO THE UNDERSIGNED
ATTORNEY OF RECORD.

Respectfully,


Michael E. Marion, Reg. 32,266
Attorney of Record




FIG. 1